

Metered Insertion

*Labor-saving Automation Equipment
Automatically fills extruded lineals*



- Automatically inserts ULTRAFAB's standard or patented T-Loc® weatherseals into aluminum or vinyl sash and frame lineals
- Problem-free filling at the rate of up to 3,000 feet/hour (6fps)
- Operates with electrical power and compressed air
- Up to 70% increased productivity versus hand pulling insertion
- Durable mechanical design assures safe, reliable operation
- ULTRAFAB's patented T-Loc® base eliminates gluing or staking of the weatherseal
- Customizable for all sash and frame shapes
- Jog feature pushes out an end for easy starting of the pile insertion
- Pneumatic brake stops the reel from over-running after each insertion
- Program in the desired length and it automatically fills the lineal
- Automatic cutter cuts weatherseal to a tolerance of one inch
- Built-in safety features include tamperproof fasteners and full guarding
- This product is available on loan to customers using over two million feet of ULTRAFAB's products annually
- Training and technical assistance are included with every machine

ULTRAFAB[®]

Tel: 800-535-1050 or 585-924-2186
email: sales@ultrafab.com
Fax: 585-924-7680
1050 Hook Road, Farmington, NY 14425
website: www.ultrafab.com

SPECIFICATIONS

Speed:	6 fps
Profiles:	All configurations
Pile Heights:	.140" to .500" (3.6 to 12.7mm)
Backing Widths:	.187" to .310" (4.7 to 7.9mm)
Electrical:	115 VAC 60Hz
Air Pressure:	80 psi clean dry air
Dimensions:	54" H x 26" W x 36" L
Weight:	106 lbs