

# Non-metered Insertion

## Labor-saving Automation Equipment Automatically fills extruded lineals



- Automatically inserts ULTRAFAB's standard or patented T-Loc® weatherseals into aluminum or vinyl sash and frame lineals
- Problem-free filling at the rate of up to 3,000 feet/hour (6fps)
- Operates with compressed air
- Up to 70% increased productivity versus hand pulling insertion
- Durable mechanical design assures safe, reliable operation
- ULTRAFAB's patented T-Loc® base eliminates gluing or staking of the weatherseal
- Customizable for all sash and frame shapes
- Pneumatic brake stops the reel from over-running after each insertion
- Pneumatic cutter cuts weatherseal
- Built-in safety features include tamperproof fasteners and full guarding
- This product is available on loan to customers using over one million feet of ULTRAFAB's products annually
- Training and technical assistance are included with every machine
- Table top mount available to conserve floor space

**ULTRAFAB**<sup>®</sup>

Tel: 800-535-1050 or 585-924-2186  
email: [sales@ultrafab.com](mailto:sales@ultrafab.com)  
Fax: 585-924-7680  
1050 Hook Road, Farmington, NY 14425  
website: [www.ultrafab.com](http://www.ultrafab.com)

### SPECIFICATIONS

Speed:	6 fps
Profiles:	All configurations
Pile Heights:	.140" to .500" (3.6 to 12.7mm)
Backing Widths:	.187" to .310" (4.7 to 7.9mm)
Air Pressure:	80 psi clean dry air
Dimensions:	31" H x 17" W x 24" L
Weight:	45 lbs