

## SOFT TOUCH FIN<sup>®</sup>

**Soft Touch Fin's non-woven barrier protection provides an excellent seal for very low friction**

Ultrafab's unique ultrasonic welding assembles the fin, fibers and backing into an integrated, unified assembly that won't break apart during fabrication or while in use.



### SOFT TOUCH FIN WEATHERSEAL FEATURES:

- Soft Touch Fin weatherseals have the structural integrity and consistency which assures a tight seal and barrier against air and water infiltration
- Solid polypropylene backing inserts more easily, saving time and reducing waste
- Pile height and backing width are always uniform because of Ultrafab's unique ultrasonically welded manufacturing systems
- No possibility of an off-center pile that binds, breaks or stretches in an extrusion
- Excellent for applications that require a quiet operating seal
- **Pile Heights:** .130" (3.30mm) to .750" (19.05mm)
- **Pile Densities:** Light, medium, high or very high
- **Backing Widths:** .180" (4.57mm), .187" (4.75mm), .200" (5.08mm), .210" (5.33mm), .229" (5.82mm), .250" (6.35mm), .270" (6.86mm), .310" (7.87mm)
- **Backing Options:**

Standard:	all backing widths
Ultra-Loc <sup>®</sup> :	S7 – .180" (4.57mm) .187" (4.75mm)
	.200" (5.08mm) .210" (5.33mm)
	.270" (6.86mm) .310" (7.87mm)
	S9 – .180" (4.57mm) .187" (4.75mm)
	.200" (5.08mm) .210" (5.33mm)
	.229" (5.82mm) .270" (6.86mm)
	.310" (7.87mm)
- **Adhesive:** Available on .187", .270" and .310"
- **Colors:** Black, white, grey and beige

**Need more fins?**  
 Ask about our *Tri-Fin<sup>®</sup>*,  
*Ultra Reach<sup>®</sup> Fin* or  
*Multi-Fin<sup>®</sup>*