

SOFT TOUCH FIN[®]

Soft Touch Fin's non-woven barrier protection provides an excellent seal for very low friction

Ultrafab's unique ultrasonic welding assembles the fin, fibers and backing into an integrated, unified assembly that won't break apart during fabrication or while in use.



SOFT TOUCH FIN WEATHERSEAL FEATURES:

- Soft Touch Fin weatherseals have the structural integrity and consistency which assures a tight seal and barrier against air and water infiltration
- Solid polypropylene backing inserts more easily, saving time and reducing waste
- Pile height and backing width are always uniform because of Ultrafab's unique ultrasonically welded manufacturing systems
- No possibility of an off-center pile that binds, breaks or stretches in an extrusion
- Excellent for applications that require a quiet operating seal
- **Pile Heights:** .130" (3.30mm) to .750" (19.05mm)
- **Pile Densities:** Light, medium, high or very high
- **Backing Widths:** .180" (4.57mm), .187" (4.75mm), .200" (5.08mm), .210" (5.33mm), .229" (5.82mm), .250" (6.35mm), .270" (6.86mm), .310" (7.87mm)
- **Backing Options:**

Standard:	all backing widths
Ultra-Loc [®] :	S7 – .180" (4.57mm), .187" (4.75mm), .200" (5.08mm), .210" (5.33mm), .270" (6.86mm), .310" (7.87mm)
	S9 – .180" (4.57mm), .187" (4.75mm), .200" (5.08mm), .210" (5.33mm), .229" (5.82mm), .270" (6.86mm), .310" (7.87mm)
Ultra Grip [®] :	.180" (4.57mm), .187" (4.75mm), .200" (5.08mm), .229" (5.82mm), .255" (6.48mm), .270" (6.86mm)
- **Adhesive:** Available on .187", .270" and .310"
- **Colors:** Black, white, grey and beige

Need more fins? Ask about our Tri-Fin[®], Ultra Reach[®] Fin or Multi-Fin[®]