

Ultra-Grip®

**Stay-in-place Backing
will not shift or slide
once inserted**



- Solid polypropylene backing inserts more easily, saving time and reducing waste
- Ultra-Grip® backing has legs on the backing which hold the backing in place
- No possibility of off-center pile that binds, breaks or stretches in an extrusion
- ULTRAFAB's unique ultrasonic welding assembles the fin, fibers and backing into an integrated, unified assembly that won't break apart during fabrication or while in use
- Ultra-Grip® is designed to be inserted using ULTRAFAB's patented automation equipment which can be used by either fabricators or extruders

Ultra-Grip® is also available on Extruded Component T-slot profiles

ULTRAFAB®

Tel: 800-535-1050 or 585-924-2186
 email: sales@ultrafab.com
 Fax: 585-924-7680
 1050 Hook Road, Farmington, NY 14425
 website: www.ultrafab.com

Ultra-Grip® Pile Weatherstripping Choices

Pile Heights:

Inch	.130" to .500"
(millimeters)	(3.30) to (12.70)

Pile Densities: Light, Medium, High or Very High

Standard Backing Widths:

Inch	.187	.200	.210	.229	.270
(millimeter)	(4.75)	(5.08)	(5.33)	(5.82)	(6.86)

Available on all standard backing widths

Colors:

Standard: Black, White, Grey, Beige, Brown

TO ORDER: See PART ORDERING SPECIFICATION SHEET